

## DULUX PROFESSIONAL Total Prep

**PRODUCT CODE** 664-89049

**Data Sheet No.** AUDD1169

**APPROVALS** APAS-0163/2, APAS-0172

### Description

DULUX PROFESSIONAL Total Prep is a high quality, 100% acrylic primer/sealer/undercoat, with excellent opacity, adhesion, flow and sealing and filling properties. It is suitable for interior and exterior use on a variety of surfaces.

### Features

Extremely high opacity  
 Excellent adhesion  
 Recoatable with all systems  
 Water based  
 Multipurpose

### Benefits

Obliterates substrate allowing 2 coat system, saves application time.  
 Sticks to substrates increasing life of paint system.  
 Use under acrylic or oil based topcoats, 1 product does it all.  
 Easy clean up, low odour.  
 One product primes, seals and undercoats.

### Uses

Use DULUX PROFESSIONAL Total Prep as a water based primer/sealer/undercoat on all interior and exterior brick, masonry, render, concrete, Hardiflex, paper faced wallboard, sound timber, Zincalume, galvanised iron, suitably primed metal and previously painted surfaces. All Dulux Professional water based and oil based topcoats can be used over this product.

### Performance Guide

**Weather** Excellent when used as part of approved system.

**Heat** Up to 70C.

**Water** Excellent when topcoated with approved topcoat.


**Solvent** Sensitive to aromatic hydrocarbons, alcohols and ketones.

**Abrasion** Good when topcoated.

### Typical Properties and Application Data

**Gloss Level** Flat

**Thinner** Water

**Gloss Level Ind**

**Spread Rate** 14.1 sqm/L

**Volume Solids** 41.0

**Components** 1

**Colour** White, may be tinted up to 28ml (1Y) per litre.

**Toxicity** Lead free. Dry film is non-toxic.

**V.O.C Level** < 60g/L untinted

**Sanding Properties** Excellent

**Wet film per coat** Recommended 71 µm

**Touch Dry** 30 Minutes

**Dry film per coat** Recommended 29 µm

**Clean Up** Clean all equipment with water.

**Recoat** 2 Hours

**Application Method**


# DULUX PROFESSIONAL Total Prep

<b>Data Sheet No.</b>	<b>AUDD1169</b>
-----------------------	-----------------

## Application Guide

### Surface Preparation

All surfaces must be thoroughly clean and free of all loose dirt, grease, mould, surface chalk and loose or flaking paint. New timber surfaces should be sanded smooth and dusted down prior to priming. Fill nail holes, imperfections and cracks with a suitable filler, sand and dust off.

For plaster surfaces use sealer binder as the precoat.

### Application Procedure and Equipment

Stir contents thoroughly before and during use. Apply direct from the can. May be applied to dampened surfaces. If applied over dry, porous surfaces, dampen surface before applying.

Brush: Wet brushes with water prior to use to avoid clogging. Apply a full even coat direct from the container. Under hot conditions it may be necessary to thin with up to 100ml per litre of clean water.

Roller: Using a medium nap roller apply a full even coat direct from the container and finish by light parallel strokes with a dry roller.

Airless/Conventional Spray: Suitable for application by all standard spray equipment. If necessary thin with up to 100ml per litre of water to aid atomisation.

NOTE: Spray application is not recommended for priming timber surfaces.

Roller, Brush & Spray

## Health and Safety

**MSDS Number** 10987

**Health Effects** For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service. Splashes to the eye may cause eye irritation. When spraying, inhalation of mists may produce respiratory irritation.

**Protective Equipment** Personal Protective Equipment: Wear eye protection and when spraying wear a dust mask.

**In the case of emergency please call 1800 033 111**

## Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.

Do not overspread or exceed 14.0 square metres per litre per coat. In hot weather, rinse brush every half hour or use two and keep one standing in water. Do not apply if temperature is under 10C, or when temperature of surface may fall below 10C during the drying period, otherwise film formation will not be complete and poor properties will result.

## Transport and Storage

**Pack A** 664-89049

**Sizes** 4 Litre 10 Litre 15 Litre

**Weight** 5.4 Kg 13.4 Kg 20.1 Kg

**Dangerous Goods Class** NA

**Shipment Name** Not dangerous goods. No special transport requirements.

**Flash point** NA

**UN Number** NA

**Package Group** NA

<b>Data Sheet</b>	DULUX PROFESSIONAL Total Prep		
<b>DuSpec Data Code</b>	AUDD1169	<b>Page No</b>	2 of 3
<b>Issue No</b>	16.0	<b>Date Issued</b>	21/06/2010



# DATA SHEET



<b>DULUX PROFESSIONAL Total Prep</b>	
	<b>Data Sheet No. AUDD1169</b>

### Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

<b>Data Sheet</b>	DULUX PROFESSIONAL Total Prep		
<b>DuSpec Data Code</b>	AUDD1169	<b>Page No</b>	3 of 3
<b>Issue No</b>	16.0	<b>Date Issued</b>	21/06/2010